

APPplay_CARplay & Android Auto set BMW/MINI iDrive CCC (CVBS)



Requirement

AUDIO OUTPUT	The interface inserts ONLY video signals into the infotainment. It is essential to have an Aux-in, when using audio from the APPplay box
VIDEO OUTPUT	Video goes via AV3
CONTROL	You can control APPplay via the original iDrive controller
SCREEN	Interface is compatible with iDrive Professional 6.5" & 8.8"
OPEN HU	Not need to open the monitor
FRONT CAMERA	The front camera input will automatically switch after leaving the reverse gear. You can set the display time in seconds via the OSD menu (1-15 sec). It is also possible to select the FRONT camera input manually
OEM REAR CAMERA	The interface does not switch back automatically to the OEM rear camera input when the reverse gear is engaged (<i>with auto gear box</i>).
GUIDELINES	Static lines are available via the interface OSD menu
iPAS	iPAS option is NOT available
PIP	PiP option is available for original parking sensor overlay (Picture in Picture)
REAR SELECT CAMERA INPUT	Interface will respond on CAN for cars with auto gearbox. When manual gear box please use the rear detection wire.
INSTALLATION	We recommend that the installation will be performed by a qualified specialist
EXTRA NOTE	PiP function = split screen iDrive CCC controllers with resistance on the end of the iDrive menu (force feedback") --> APPplay control via iDrive not possible. You must use an external controller.